

# BRUSH VENT

## RIGID UNDER-RIDGE WITH SIDE BRUSHES

### FAST INSTALLATION

Thanks to its soft bristles, it adapts easily to the profile of the cover without the need for shaping.

### PROTECTION

The bristles provide effective protection against the intrusion of water and foreign elements.




### TECHNICAL DATA

| Properties             | value                    | USC units                  |
|------------------------|--------------------------|----------------------------|
| Materials              | PVC                      | -                          |
| Screen length          | 60 mm                    | 2.36 in                    |
| Air passage            | ≥ 200 cm <sup>2</sup> /m | ≥ 9.45 in <sup>2</sup> /ft |
| UV resistance          | permanent                | -                          |
| Temperature resistance | -20 / +80 °C             | -4 / +176 °F               |

Waste classification (2014/955/EU): 17 02 03.

### CODES AND DIMENSIONS

| CODE                        | B<br>[mm] | H<br>[mm] | L<br>[m] | B<br>[in] | H<br>[in] | L<br>[ft] | colour    | RAL  |  |
|-----------------------------|-----------|-----------|----------|-----------|-----------|-----------|-----------|------|---|
| BRUVENRED175                | 175       | 75        | 1        | 6.9       | 3.0       | 3         | brick red | 8004 | 20  |
| BRUVENBRO175 <sup>(1)</sup> | 175       | 75        | 1        | 6.9       | 3.0       | 3         | brown     | 8019 | 20  |
| BRUVENBLA175                | 175       | 75        | 1        | 6.9       | 3.0       | 3         | black     | 9005 | 20  |

<sup>(1)</sup>Products available only upon order.

### RECOMMENDATIONS FOR INSTALLATION

