

# START BAND



## WATERPROOF PROFILE WITH HIGH MECHANICAL RESISTANCE



### ELASTICITY

Thanks to its elasticity, it is extremely easy to install even around corners and it is resistant to perforations or mechanical fastening.

### DURABILITY

It is compatible with bitumen, it does not degrade and it is UV-resistant. It is resistant to walking wear and cold temperatures.



1 START BAND



2 START BAND ADHESIVE

## COMPOSITION

support: EPDM-based synthetic rubber

## TECHNICAL DATA

| Properties                               | standard           | value      | USC units     |
|--|--------------------|------------|---------------|
| Water vapour transmission (Sd)           | EN ISO 12572       | 40 m       | 0.09 US Perm  |
| Water vapour resistance factor (μ)       | EN 1931            | 50000      | 200 MN-s/g    |
| Tensile strength                         | DIN 53504          | ≥ 7,0 MPa  | -             |
| Elongation                               | DIN 53504          | ≥ 300%     | -             |
| Resistance to nail tearing               | DIN 53504          | ≥ 10 kN/m  | ≥ 2.25 lbf/in |
| Watertightness                           | EN 1928            | compliant  | -             |
| Durability:                              |                    |            |               |
| - watertightness after artificial ageing | EN 1296/EN 1928    | compliant  | -             |
| - in the presence of alkalis             | EN 1847/EN 12311-2 | npd        | -             |
| Reaction to fire                         | EN 13501-1         | class E    | -             |
| Resistance to temperature                | -                  | -30/+75 °C | -22/+167 °F   |
| Application temperature                  | -                  | -10/+35 °C | +14/+95 °F    |

Store the product in a dry, covered location.

Waste classification (2014/955/EU): 17 02 03.

## CODES AND DIMENSIONS

| CODE | B         | s    | L   | B    | s     | L    |    |    |
|------|-----------|------|-----|------|-------|------|----|----|
|      | [mm]      | [mm] | [m] | [in] | [mil] | [ft] |    |    |
| 1    | START100  | 100  | 0,8 | 20   | 3.9   | 32   | 66 | 12 |
|      | START150  | 150  | 0,8 | 20   | 5.9   | 32   | 66 | 8  |
|      | START200  | 200  | 0,8 | 20   | 7.9   | 32   | 66 | 5  |
|      | START250  | 250  | 0,8 | 20   | 9.8   | 32   | 66 | 5  |
| 2    | STARTA120 | 120  | 0,8 | 20   | 4.7   | 32   | 66 | 12 |
|      | STARTA160 | 160  | 0,8 | 20   | 6.3   | 32   | 66 | 3  |

## ■ FIELDS OF APPLICATION



## ■ RELATED PRODUCTS



CUTTER  
page 394



PRIMER SPRAY  
page 112



HAMMER STAPLER 22  
page 396



DOUBLE BAND  
page 68



### WIDE RANGE, INCLUDING ADHESIVE

Also available in an adhesive version (STARTA120 and STARTA160), ideal when applied in combination with ALU START, for an infallible connection to the ground.

### SAFETY

It protects walls and foundation walls against rising damp over time, even at extreme temperatures. Also suitable as a general damp-proof course barrier.