

# RIDGE

## NET ROLL

### FLEXIBLE VENTILATED UNDER-RIDGE

#### FLEXIBLE

The polypropylene ventilation fabric ensures excellent adaptability during installation.

#### DOUBLE SECURITY

The ventilation strip, which is sewn and glued to the pleated wings, guarantees that the solution remains intact during installation and continues to be effective over time.



### TECHNICAL DATA

| Properties                                     | value                          | USC units                |
|------------------------------------------------|--------------------------------|--------------------------|
| Air passage                                    | approx. 150 cm <sup>2</sup> /m | 7.09 in <sup>2</sup> /ft |
| Elongation capacity (pleated aluminium strips) | approx. 45 %                   | -                        |
| Butyl tape width                               | 15 mm                          | 0.6 in                   |
| Butyl tape thermal resistance                  | -40 / +90 °C                   | -40 / +194 °F            |
| Application temperature                        | +5 / +40 °C                    | +41 / +104 °F            |
| UV resistance (aluminium straps)               | permanent                      | -                        |
| Storage temperature <sup>(1)</sup>             | +5 / +30 °C                    | +41 / +86 °F             |

<sup>(1)</sup> Keep the product in a dry, covered location.

 Waste classification (2014/955/EU): 17 09 04.

### CODES AND DIMENSIONS

| CODE        | B<br>[mm] | L<br>[m] | B<br>[in] | L<br>[ft] | colour    | RAL  |  |
|-------------|-----------|----------|-----------|-----------|-----------|------|---------------------------------------------------------------------------------------|
| NETRED310   | 310       | 5        | 12.2      | 16        | brick red | 8004 | 4                                                                                     |
| NETBRO310   | 310       | 5        | 12.2      | 16        | brown     | 8019 | 4                                                                                     |
| NETBLA310   | 310       | 5        | 12.2      | 16        | black     | 9005 | 4                                                                                     |
| NETRED390   | 390       | 5        | 15.4      | 16        | brick red | 8004 | 4                                                                                     |
| NETBRO390   | 390       | 5        | 15.4      | 16        | brown     | 8019 | 4                                                                                     |
| NETBLA390   | 390       | 5        | 15.4      | 16        | black     | 9005 | 4                                                                                     |
| NETRED39020 | 390       | 20       | 15.4      | 66        | brick red | 8004 | 1                                                                                     |
| NETBRO39020 | 390       | 20       | 15.4      | 66        | brown     | 8019 | 1                                                                                     |
| NETBLA39020 | 390       | 20       | 15.4      | 66        | black     | 9005 | 1                                                                                     |



#### EASY TO SHAPE

Aluminium straps and butyl tape ensure adaptability to the profile of the roof elements.

#### MATERIALS

Aluminium, PP non-woven fabric, butyl tape.