


CLIPS


TILE STOP L

L PRE-SHAPED HOOKS FOR PLAIN TILES

- Dry installation
- Tough and secure hold for the first row of tiles on the pitch
- They can be used as mullion hooks on which the weight of the upper rows of tiles can be unloaded
- Installation with foam or mortar is avoided in compliance with standard UNI 9460
- Wide range of materials and sizes available



CODES AND DIMENSIONS

| CODE | L [mm] | H [mm] | L [in] | H [in] | material | colour | RAL |  |
|----------------------------|-----------|-----------|-----------|-----------|-------------------------|-----------|------|---------------------------------------------------------------------------------------|
| TSLI28016 ⁽¹⁾ | 280 | 16 | 11.0 | 0.6 | steel AISI 204 | steel | - | 200 |
| TSLI28020 ⁽¹⁾ | 280 | 20 | 11.0 | 0.8 | steel AISI 204 | steel | - | 200 |
| TSLRED28016 ⁽¹⁾ | 280 | 16 | 11.0 | 0.6 | pre-painted metal sheet | Siena red | 3009 | 200 |
| TSLRED28020 ⁽¹⁾ | 280 | 20 | 11.0 | 0.8 | pre-painted metal sheet | Siena red | 3009 | 200 |
| TSLBRO28016 ⁽¹⁾ | 280 | 16 | 11.0 | 0.6 | pre-painted metal sheet | brown | 8019 | 200 |
| TSLBRO28020 ⁽¹⁾ | 280 | 20 | 11.0 | 0.8 | pre-painted metal sheet | brown | 8019 | 200 |
| TSLCOP28016 ⁽¹⁾ | 280 | 16 | 11.0 | 0.6 | stainless steel tape | copper | - | 200 |
| TSLCOP28020 ⁽¹⁾ | 280 | 20 | 11.0 | 0.8 | stainless steel tape | copper | - | 200 |

⁽¹⁾Products available only upon order.

 Waste classification (2014/955/EU): 17 04 05.

RECOMMENDATIONS FOR INSTALLATION

