MULTI BAND

SPECIAL HIGH-ADHESION TAPE, CAN BE PLASTERED

D
DIN 4108-7

CAN BE PLASTERED
HIGH STABILITY

EXCELLENT ADHESION
Its excellent adhesion makes it ideal for application on most surfaces, even at low temperatures.

CAN BE PLASTERED
Technical fabric perfect for subsequent plastering, ensuring excellent visual appeal by allowing the tape to be concealed behind claddings and plaster.



COMPOSITION

1. **support:**: breathable 2-layer PP membrane
2. **adhesive:** acrylic dispersion without solvents
3. **release liner:** silicone coated paper

TECHNICAL DATA

Properties	standard	value	*USC units*
Thickness	-	0,6 mm	*24 mil*
Tensile strength	EN ISO 29864	44,0 N/10 mm	*25.1 lbf/in*
Adhesion strength on OSB at 90° after 10 minutes	EN 29862	5,0 N/10 mm	*2.9 lbf/in*
Adhesion strength on OSB at 180° after 10 minutes	EN 29862	9,0 N/10 mm	*5.1 lbf/in*
Adhesion strength (average) on membrane in PP after 24 hours(1)	EN 12316-2	15,0 N/50 mm	*1.7 lbf/in*
Shear adhesion strength of the joint on membrane in PP after 24 hours(1)	EN 12317-2	150,0 N/50 mm	*17.1 lbf/in*
Water vapour transmission (Sd)	EN 1931	< 1 m	*> 3.5 US Perm*
Exposure to weather	-	3 months	-
Application temperature(3)	-	> -10 °C	*> +14 °F*
Resistance to temperature	-	-40/+100 °C	*-40/+212 °F*
Storage temperature(3)	-	+5/+25 °C	*+41/+77 °F*
Solvents	-	no	-

(1)Minimum required value according to DTU 31.2 P1-2 (France): 15 N/50 mm.
(2)Minimum required value according to DTU 31.2 P1-2 (France): 40 N/50 mm.
(3) On dry support and at a temperature > 0 °C. The absence of condensation or frost on the surface must be guaranteed.
(4)Store the product in a cool, dry place for no more than 12 months.

Waste classification (2014/955/EU): 08 04 10.

CODES AND DIMENSIONS

CODE	liner [mm]	B [mm]	L [m]	*liner [in]*	*B [in]*	*L [ft]*	
MULTI60	60	60	25	*2.4*	*2.4*	*82*	10

rothoblaas

FIELDS OF APPLICATION









RELATED PRODUCTS



PRIMER SPRAY



PLASTER BAND IN



PLASTER BAND OUT



PLASTER BAND LITE



UNIVERSAL

Excellent for sealing the membranes overlapping both inside and outside.

SAFE

Thanks to its special composition, it prevents the uncontrolled passage of air, ensuring constantly perfect air and wind tightness.